NovoTouch

TK series

An Interactive solution tailored for Educational and Business needs





Overview



The NovoTouch TK series presents a comprehensive interactive solution equipped with a Multi-touch screen, wireless collaboration features, and robust software tailored for both educational and corporate environments. Available in display sizes of 65", 75", and 86", it elevates business meetings and educational sessions by fostering enhanced collaboration and interaction.

٠

- 4K-UHD resolution
- Backlit D-LED IPS panel
- Multi-point IR touch
- Multiple I/O Interfaces
- Whiteboard

- Wireless collaboration (NovoConnect)
- 4 Split Screen with FHD resolution
- Support NT Minutes/NT LiveScreen
- NT LiveNote
 - Floating App





4K-UHD Resolution

The TK series features 65"/75"/86" display size with 4K Ultra-HD (3,840 x 2,160) resolution to deliver outstanding details and stunning visuals..







Backlit D-LED Technology

Backlit D-LED (IPS panel) technology offers brighter pictures, flawless colors, richer textures, and extra wide viewing angels $(178^{\circ}/178^{\circ})$ with an incredibly sharp and crisp images.



- 1.07 billion displayable colors
- High color consistency
- High contrast ratio



- 178° Hyper-Viewing Angle
- Color accuracy from all viewable angles



Interactive IR Touch Technology

The TK series supports 20-point interactive touch capability (10-point writing, 20-point touch). Infrared Touch (IR) technology ensures flawless touch annotation, high accuracy, and fast response time






Wireless Collaboration

The TK series has built-in NovoConnect wireless presentation and collaborative system for cable-free and hassle-free presenting in the classroom or in office.

NovoConnect App/ Software



Simply control and share from BYODs using the NovoConnect App.








Great Connectivity: Multiple I/O Interfaces

The multiple interfaces, such as USB Type-C, HDMI, and USB2.0/3.0, allow you to easily connect to various devices. In addition to support up to 65W power supply, fully functional USB Type-C also supports video input up to 1080P 60Hz.





Dual Ethernet Interfaces

The TK series has dual Ethernet interfaces. When there is only one network port in the use environment, the dual Ethernet interface can share the same network port with other devices.





NT Minutes & NT LiveScreen

The TK series supports screen recording (NT Minutes) and screen content sharing (NT LiveScreen).



NT Minutes

Screen recording, prepare for e-Learning materials, review the lesson and share with others.

NT Screen Broadcasting Duplicate to a hub of multiple NovoTouch Panels






NT Minutes Screen

NT Minutes				NT Minutes Record Screen) Settings			
3	00:00:00			Bit Rate: 4 Resolution: 1 Countdown seconds: 3 Time limit (Hour): 2 Size limit (GB): 2 Current Storage Folder: // ♥ Floating ToolBar ♥ Floating ToolBar ♥ Microphone	920x1080 2 2	* * * *	2	0	
		Current Storage Folder: /Movies/NT-Minutes	18.2 GB available / 21.73 GB in total				Current Storage Folder: /Movies/NT-Minutes	18.2 GB available / 21.73 GB in 1	total



Screen Broadcast





4 Split Screen with FHD Resolution

Up to 64 participants can be connected and up to 4 can share their screen simultaneously. The TK series each split screen has 1080p high resolution.





NT LiveNote

The TK series supports real-time annotation on the screen. Users can make "live" annotations on any screen, so that meetings or lectures can be uninterrupted and the screen can be used more smoothly.


NFI T/



Floating Apps




Users can open more apps at the same time in floating windows and enjoy multitasking. Take notes or use calculator anywhere and anytime.





Launch-pad


The TK series features a new Launch-pad function similar-to the program overview, users can quickly find the APP they need by launch-pad.



57,4.20 Sui $h_1 = h_2$ 66 Suz 3 0 Redo 30 NovoConnect NT Timer NT Calculator NT Highlighter Chrome File explorer



Android & Software



- Android version 13
- Google Play Store I NT Play Store
- Built-in Apps for collaboration
- Chrome I NT Browser



Home Screen






App Screen





Whiteboard Basic Features


- Basic functions: pen, highlighter, eraser, shape, text, etc.
- Teaching tools : form, puzzle bag, sticky note, spotlight, etc.





Whiteboard Dual-Tip pen


- Dual-tip pen Each tip-type (fine or thick) can have its own drawing color.
- Lightweight with classic pen design






Whiteboard Handwriting

- Handwriting text recognition
 - Convert written text to easily readable digital text
- Sketch recognition (shape recognition)
 - Convert hand-drawing shapes (like triangle) to perfectly-rendered digital shapes








Whiteboard Multi-Canvas


- Partition whiteboard surface into regions, each of which is independent canvas for writing and drawing
- Ideal for group teaching






Whiteboard Split +

- Divide Whiteboard S/w into 2 parts with full functionality of whiteboard surface
- Ideal for teaching with multi screen / multiple backgrounds at the same time.











Whiteboard And more...


- Embed PDF, video, and webpage, etc.
- Shared by QR code
- Customizable background color and image



TK I/O Ports




Optional Accessory





Standard Accessory





Appendix



Product Specification

Model	TK652i	TK752i	ТК862і				
Display Technology	Backlit LED (IPS Panel)						
Panel Size	65"	75"	86"				
Brightness	400cd/m2						
Contrast Ratio	1200:1 (DCR: 30,000:1)						
Native Resolution	4K-UHD (3840 x 2160)						
Viewing Angle(H/V)	178° / 178°						
Aspect Ratio	16:9						
Response Time (MS)	8ms						
Touch Technology	Infrared Touch						
Touch Points	20 Point (Standard)						
Refresh Rate (Hz)	60Hz						
Display Color (Bit)	1.07 billion						
Installation Orientation	Landscape						
Daily Operation (Hours/Days)	16/7						
Dimensions (WxDxH)	1,484.5 x 90 x 908 mm	1744 x 1070 x 107mm	1990 x 1208 x 107mm				
Weight	39kg (85lbs)	62 kg (136.7 lbs)	76 kg (167.5 lbs)				
VESA Mounting	4 – M8 × 25mm, 800 x 600mm	4 – M8 × 25mm, 800 x 400mm	4 – M8 × 25mm, 800 x 400mm				
Power Supply	AC 100-240V, 50/60Hz						



